

Floor Patch Pro

Provides SUPERIOR Performance at a Value!

Polymer-modified, cement-based skim coat and patching product. Ideal for jobs with deeper needs and slabs with high humidity.

- **15 minute set time**
 - Accepts most floor coverings in as little as 30 minutes
- **Low dust when sanded**
 - Less dust to interfere with floor covering bond
 - Less time wasted on clean up
- **Installs on slabs with up to 90% relative humidity**
- **Superior workability and coverage for quick and easy application**
 - Featheredge to 2"



See the Difference – Superior Performance at a Value!

TECHNICAL DATA	ProSpec® Floor Patch Pro ¹	Mapei Planipatch ²
Working Time	10 to 12 minutes	8 to 10 minutes
Set Time	15 minutes	Not Available
Ready For Most Floor Covering	15 to 30 minutes*	60 to 90 minutes*
Minimum Thickness	Featheredge	Featheredge
Maximum Thickness (Neat)	2"	1/2"
28 Day Compressive Strength	> 4,000 psi	> 3,500 psi
Yield Per 25 lb. Bag @ 1/8"	approximately 39 sq. ft.	25 to 35 sq. ft.
Acceptable Slab Relative Humidity	Up to 90%	Up to 85%

¹Based on Floor Patch Pro Technical Data Sheet - 7/12 edition

²Based on Mapei Technical Data Sheet - 3/16/10 edition

*or when completely dry



Visit prospec.com to learn more



H.B. Fuller Construction Products Inc.
 1105 South Frontenac Street
 Aurora, IL 60504-6451 U.S.A.
prospec.com