

PermaSet® Tile Setting Mortars

Non-Modified Series



Description	PermaSet® 200	PermaSet® 275
	Designed for installing ceramic tile on interior concrete floors.	Designed for installing ceramic tile on interior walls or floors.
Technical Standards:		
ANSI Standard when mixed with water	A118.1	A118.1
ANSI Standard when mixed with ProSpec® B-730 Mortar / Acrylic Additive	A118.4 & A118.11	A118.4 & A118.11
ISO 13007 Standard	C1	C1
ISO 13007 Standard when mixed with ProSpec® B-730 Mortar / Acrylic Additive	C2P1	C2P1
Installs where:		
	Interior/Exterior ¹	Interior/Exterior ¹
	Floors	Floors/Walls
Ideally designed for the installation of:		
Large format tile (LFT) ²		
Ceramic tile	■	■
Porcelain	■ ¹	■ ¹
Quarry	■	■
Non-moisture sensitive natural stone	■ ¹	■ ¹
Cement tile		
Pavers		
High bottom lugged tile		
Glass tile		
Installs over substrates:		
Concrete	■	■
Cement backerboard (CBU)	■	■
Cured portland cement mortar	■	■
Exterior grade plywood	16" OC Max ¹	16" OC Max ¹
Masonry		■
Waterproofing		■
Gypsum plaster or gypsum board ³		■
VCT		
Cutback adhesive		
Tile over tile		■
Uncoupling membrane ⁴	■	■
Cork underlayment		
Countertops		

1. When mixed with B-730 Mortar / Acrylic Additive

2. Large format tile is defined as any tile or stone with one side ≥ 15" (381 mm)

3. Residential Dry (RES1) / Commercial Dry (COMM1) only

4. Follow manufacturers recommendations