

1. PRODUCT NAME

ProSpec[®] Level Set[®] Primer Plus

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.

1-800-552-6225 Office
1-800-952-2368 Fax
prospec.com

3. PRODUCT DESCRIPTION

ProSpec[®] Level Set[®] Primer Plus is a highly concentrated film-forming dispersion for priming very dense, smooth, non-absorbent substrates such as terrazzo, marble, metal decking, ceramic and quarry tile.

Features and Benefits

Provides maximum adhesion and seal between the substrate and the underlayment or topping

- Solvent free
- Water-based
- Rapid drying
- Excellent bond
- Non-flammable

Uses

For use over:

- Most non-porous subfloors
- Moisture mitigation coatings
- Steel
- Properly prepared cutback adhesive or non-soluble adhesive residue
- Wooden substrates including plywood

Note: All Level Set[®] products must be used in conjunction with a Level Set[®] primer. See individual product data sheets.

SAFETY

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS Sheets are available on our website prospec.com or contact Medical Emergency Phone Number (24 Hours): 1-888-853-1758, Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300 or contact ProSpec[®] Technical Services at 800-832-9023 (7:00AM to 5:00PM M-F, Central US Time).

CAUTIONS

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered ProSpec[®] brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Color Wet/Dry	Green/Green
Density	8.3 lb / gal (1.0 kg / L)
Drying Time	1 - 2 hours @ 70°F (21°C)
Flash Point	None
Flammability	Non-flammable
Additional Information	Water-based

VOC

< 20 g/l

LEED[®] Eligibility¹

- Low-Emitting Materials (IEQ-c4.2)

Packaging

2.64 gal / jug (10 L) - Product #65510026

Shelf Life

24 months from the date of manufacture when stored in the original, unopened container, away from moisture, under cool, dry conditions and out of direct sunlight.

5. INSTALLATION Preparation

- All materials should be stored at 40°F (4°C) to 80°F (27°C) 24 hours prior to installation.
- Surface must be clean, dry, hard and free from dirt, loose particles, wax, sealers, curing compounds, grease, paint, efflorescence and any foreign materials that will inhibit adhesion.
- Weak concrete surfaces must be cleaned down to a solid sound substrate by mechanical means. Acid etching or chemical cleaning is not acceptable. Thoroughly abrade any dense, smooth or metal surfaces.
- Cutback and adhesives must be thin and have a solid bond to the subfloor. Remove all dust by vacuuming.
- Reference Level Set[®] Underlayment or Level Set[®] Wear Topping TDS for more detailed information.

Note: It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.

Job Mockups

The manufacturer requires that when its ProSpec® products are used in any application or as part of any system that includes other manufacturers' products, the contractor and/or design professional shall test all the system components collectively for compatibility, performance and long-term intended use in accordance with pertinent and accepted industry standards prior to any construction. Written documentation of the tests performed shall be satisfactory to the design professional and contractor. Test results must include the means and methods of application, products used, project-specific conditions being addressed, and standardized tests performed for each proposed system or variation.

Mixing

- Shake the container before use.
- Optimum mixing conditions are between 65°F (17°C) to 75°F (22.5°C).
- Over wood, non-absorbent or smooth substrates, use neat. Do not mix with any other additives.
- Over rough or porous cement substrates use Level Set® Primer Plus mixed 1:1 with water or Level Set® Primer.

Application

- Apply when the air and substrate temperatures are between 40°F (4°C) and 100°F (38°C). For applications outside this range of temperatures, contact ProSpec® Technical Services.
- Within one hour of shaking, apply a THIN, even coat of Level Set® Primer Plus to the substrate using a fine pore foam roller leaving no bare spots. Avoid puddles and excess accumulations. Heavy or thick applications can be detrimental to the performance and can cause cracking of the underlayment or topping.
- Do not apply with a sprayer, broom or mop.
- Allow to dry to a clear translucent green film before application of Level Set® Underlayment or Toppings. This typically takes 1 - 2 hours at 75°F (22.5°C) and 50% relative humidity. Lower temperatures and high humidity will extend the dry time and high temperatures and low humidity will shorten the dry time.
- Level Set® Primer Plus must be covered by a Level Set® underlayment or topping within 48 hours. If not covered within 48 hours reapply a thin layer of Level Set® Primer Plus following the above instructions.
- Protect the primed substrate from foot traffic.

Cleaning

- Clean equipment water and detergent immediately after use.

Limitations

- Do not use on water soluble adhesive residue.
- Do not apply with a sprayer, broom or mop.
- Do not allow to freeze. Store above 40°F (4°C).
- Do not use when polishing Wear Topping.

Coverage

Approximately 280 - 450 ft² (26 - 42 m²) per gallon depending on substrate characteristics.

6. AVAILABILITY

To locate ProSpec® products in your area, please contact:
Phone: 800-832-9002
Website: prospec.com

7. WARRANTY

For warranty details, see your sales associate or prospec.com

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the Technical Support Hotline.
Toll Free: 800-832-9023
Fax: 630-952-1235

Technical and safety literature

To acquire technical and safety literature, please visit our website at prospec.com

10. FILING SYSTEM

Division 3

¹ ProSpec® products can contribute to LEED® credits within the Material Resource, (Recycled Content & Regional Materials) and Indoor Environmental Quality (Low Emitting Materials).

©Copyright 2014
H.B. Fuller Construction Products Inc.

ProSpec® and Level Set®
are trademarks of H.B. Fuller
Construction Products Inc.

LEED® is a registered trademark of
U.S. Green Building Council.

Data Sheets are subject to change
without notice. For the latest revision,
check our website at prospec.com



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
prospec.com