

1. PRODUCT NAME

ProSpec® ProColor Advantage Caulk

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.

1-800-552-6225 Office
1-800-952-2368 Fax
prospec.com

3. PRODUCT DESCRIPTION

ProSpec® ProColor Advantage Caulk is a (Type S) elastomeric sealant and adhesive that is color and texture matched to all of the ProSpec® ProColor Grouts. This unique formula has been specifically designed for use as a cold-applied elastomeric joint sealant or caulking.

Features and Benefits

- Superior flexibility
- Non sag, gunnable sealant for vertical applications
- Color and texture match
- Paintable in 24 - 48 hours
- Adheres to aluminum, ceramics, glass, pvc, steel and wood
- Indoor/outdoor use
- Cures in wet environments
- Stain, mold and mildew resistant
- Meets ASTM C 920 and TTS 0230C for 1 step expansion joint solution

Uses

- For caulking around sinks, tubs, showers, countertops and ceramic tile floors
- As a flexible barrier/filler between horizontal and vertical surfaces to prevent cracked tile due to expansion
- For filling joints where tile meets dissimilar surfaces
- For restoring cracked or worn grout joints
- Expansion joints
- Pedestrian and vehicular traffic
- Buildings, plazas, decks, walkways or parking garages

SAFETY

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS Sheets are available on our website prospec.com or contact Medical Emergency Phone Number (24 Hours): 1-888-853-1758, Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300 or contact ProSpec® Technical Services at 1-800-832-9023 (7:00AM to 5:00PM M-F, Central US Time).

CAUTIONS

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered ProSpec® brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Classifications		
Type S	(ASTM C 920)	Single Component
Grade	(ASTM C 1183)	NS
Joint Movement (%)	(ASTM C 719)	100/50 (Unsanded) 50/50 (Sanded)
Use	(ASTM C 920)	T, G, A
Hardness	(ASTM C 661)	25-50
Accelerated Weathering	(ASTM C 793)	4,000 hours No cracking

VOC

< 10 g/l

LEED® Eligibility¹

- Regional Materials (MR-c5)
- Low-Emitting Materials (IEQ-c4.1, IEQ-c4.3, IEQ-c4.6)

Packaging

10.3 fl oz (310 ml) tubes, 4 tubes per case.

Colors

Available in all ProSpec® ProColor Grout colors.

Shelf Life

2 years from the date of manufacture when stored in the original, unopened container under cool, dry conditions and out of direct sunlight. KEEP FROM FREEZING.

Job Mockups

The manufacturer requires that when its ProSpec® products are used in any application or as part of any system that includes other manufacturers' products, the contractor and/or design professional shall test all the system components collectively for compatibility, performance and long-term intended use in accordance with pertinent and accepted industry standards prior to any construction. Written documentation of the tests performed shall be satisfactory to the design professional and contractor. Test results must include the means and methods of application, products used, project-specific conditions being addressed, and standardized tests performed for each proposed system or variation.

5. INSTALLATION

1. Apply caulk when temperature is between 40°F - 100°F (4°C - 38°C).
2. Surfaces must be dry, clean and free of dust, dirt, mildew, oil and other foreign substances.
3. Remove all old caulking or joint sealant before applying.
4. Clean area with mild solution of bleach and water. Be sure area to be caulked is completely dry before applying caulk.
5. Cut spout to desired bead thickness.
6. Puncture the foil seal inside nozzle.
7. Tool caulking within 5 minutes of application. Use wet finger or wet smooth sponge. Excess may be cleaned up with mineral spirits or denatured alcohol before caulk begins to skin over.
8. Protect from any traffic for 24 hours.
9. Allow 72 hours before opening to light traffic.
10. Caulk is fully cured in 7 days depending on temperature, humidity, and thickness of application.
11. Caulk may be painted within 24 hours with water based paint and 48 hours for an alkylid paint.

Note: Temperature and humidity will affect curing time.

This product contains colorants that may stain some porous materials such as walls, wallpaper, etc. Mask or shield these areas to protect from staining. Test in a non-conspicuous area to see if staining will occur.

Coverage

Joint Size (width x depth)	Linear Feet per 10.3 oz.
1/8" x 1/8" (3 x 3 mm)	96 (29.2 m)
1/8 x 1/4 (3 x 6 mm)	48 (14.6 m)
1/8 x 3/8 (3 x 10 mm)	32 (9.8 m)
1/8 x 1/2 (3 x 13 mm)	24 (7.3 m)
1/4 x 1/8 (6 x 3 mm)	48 (14.6 m)
1/4 x 1/4 (6 x 6 mm)	24 (7.3 m)
1/4 x 3/8 (6 x 10 mm)	16 (4.9 m)
1/4 x 1/2 (6 x 13 mm)	12 (3.7 m)
3/8 x 1/8 (10 x 3 mm)	32 (9.8 m)
3/8 x 1/4 (10 x 6 mm)	16 (4.9 m)
3/8 x 3/8 (10 x 10 mm)	11 (3.4 m)
3/8 x 1/2 (10 x 13 mm)	8 (2.4 m)

6. AVAILABILITY

To locate ProSpec® products in your area, please contact:
Phone: 800-832-9002
Website: prospec.com

7. WARRANTY

For warranty details, see your sales associate or prospec.com

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the Technical Support Hotline.
Toll Free: 800-832-9023
Fax: 630-952-1235

Technical and safety literature

To acquire technical and safety literature, please visit our website at prospec.com

10. FILING SYSTEM

Division 9

¹ ProSpec® products can contribute to LEED® credits within the Material Resource, (Recycled Content & Regional Materials) and Indoor Environmental Quality (Low Emitting Materials).

©Copyright 2014
H.B. Fuller Construction Products Inc.

ProSpec® is a trademark of
H.B. Fuller Construction Products Inc.

LEED® is a registered trademark of
U.S. Green Building Council.

Data Sheets are subject to change
without notice. For the latest revision,
check our website at prospec.com



H.B. Fuller Construction Products Inc.

1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
prospec.com