

1. PRODUCT NAME

ProSpec® ProColor Tile & Grout Caulk

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.

1-800-552-6225 Office
1-800-952-2368 Fax
prospec.com

3. PRODUCT DESCRIPTION

ProSpec® ProColor Sanded and Unsanded Tile and Grout Caulk is an easy to clean siliconized acrylic latex caulk specifically formulated for easy application and to match ProColor Sanded and ProColor Unsanded Grout colors.

Features and Benefits

- Color matched to ProColor Grout*
- Sanded and unsanded version
- For indoor and outdoor use
- Stain, mold and mildew resistant
- Paintable
- Water cleanup before cured
- Meets ASTM C 834

*Note: Slight color variation is expected due to differences in the texture and composition of materials.

Uses

- Interior and exterior applications*
- Caulk around showers, sinks, tubs, countertops and tile floors
- Fill gaps up to ¼" (6 mm)
- Where tile abuts dissimilar substrates
- Fill joints between horizontal and vertical surfaces

*Note: Exterior projects subject to intermittent water immersion only (Com2)

SAFETY

READ THE SAFETY DATA SHEET (SDS) BEFORE USING THIS PRODUCT. SDS Sheets are available on our website prospec.com or contact Medical Emergency Phone Number (24 Hours): 1-888-853-1758, Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300 or contact ProSpec® Technical Services at 1-800-832-9023 (7:00AM to 5:00PM M-F, Central US Time).

CAUTIONS

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered ProSpec® brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

Packaging

10.3 fl oz (310 mL) plastic tubes.

Shelf Life

3 years from the date of manufacture when stored in the original, unopened container, away from moisture, under cool, dry conditions and out of direct sunlight. Keep from freezing.

5. INSTALLATION Preparation

All materials should be stored at 50°F (10°C) to 90°F (32°C) 24 hours prior to installation.

- Apply when the air and substrate temperature is between 50°F (10°C) to 90°F (32°C) within 24 hours of application. The surface must remain frost free for 72 hours.
- Surface must be structurally sound, stable, clean, dry, hard and free from dirt, loose particles, paint, mildew or any foreign materials that will inhibit adhesion.
- Vacuum joints and wipe clean with a damp towel.
- Check the compatibility over porous materials prior to application as this product contains colorants that may stain some porous materials such as walls, wall paper, absorbent stone, etc. Use masking tape to protect the areas and achieve a uniform application.

Note: It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use.

Job Mockups

The manufacturer requires that when its ProSpec® products are used in any application or as part of any system that includes other manufacturers' products, the contractor and/or design professional shall test all the system components collectively for compatibility, performance and long-term intended use in accordance with pertinent and accepted industry standards prior to any construction. Written documentation of the tests performed shall be satisfactory to the design professional and contractor. Test results must include the means and methods of application, products used, project-specific conditions being addressed, and standardized tests performed for each proposed system or variation.

Application

Apply when air or substrate temperature is between 50°F (10°C) and 90°F (32°C). For applications outside this range of temperatures, contact ProSpec® Technical Services.

- Allow the tile and grout to be firmly set, typically 24 to 48 hours before caulking.
- Cut nozzle to desired bead size at a 45 degree angle.
- Completely fill the joint with ProSpec® Tile and Grout Caulk.
- Immediately smooth the surface using a wet finger or damp, smooth sponge.
- Excess may be cleaned up with a damp cloth before the caulk skins over.
- Immediately wash hands and tools with warm soap and water.
- Protect the caulk from water exposure until fully cured, which is typically 3-5 days depending on thickness, temperature and humidity. (To assist in curing the caulk in humid and enclosed areas such as an enclosed shower, use a fan to circulate the air.)
- Remove excess caulk before the caulk skins over.

Limitations

- Do not use for exterior applications subject to constant water immersion.
- Do not use in steam showers or surfaces exposed to harsh chemicals.
- Do not use areas where excessive movement or expansion and surface wear is expected.
- Do not use in joints >1/4" (6 mm). Contact Technical Services for installations with a joint width >1/4".
- Do not use in joints <1/16" (1.5 mm).
- Do not use when the temperature is outside the range of 50°F (10°C) to 90°F (32°C).
- Do not use on concrete that is less than 30 days old.

Coverage

Per 10.3 oz (310 mL).

- 1/16" (1.5 mm): 45 - 48 lin ft (13.7 - 14.6 m)
- 1/8" (3 mm): 22 - 24 lin ft (6.7 - 7.3 m)
- 1/4" (6 mm): 11 - 12 lin ft (3.4 - 3.7 m)

6. AVAILABILITY

To locate ProSpec® products in your area, please contact:
Phone: 800-832-9002
Website: prospec.com

7. WARRANTY

For warranty details, see your sales associate or prospec.com

8. MAINTENANCE

Not applicable

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the Technical Support Hotline.
Toll Free: 800-832-9023
Fax: 630-952-1235

Technical and safety literature

To acquire technical and safety literature, please visit our website at prospec.com

10. FILING SYSTEM

Division 9