

SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

- Product Name:**
1. ProSpec PermafleX 300
Product Code: Gray - 65250311 (50lb)
White - 65467516 (50lb)
 2. ProSpec PermafleX 400
Product Code: Gray - 65252890 (50lb)
White - 65252900 (50lb)
 3. ProSpec PermafleX 600
Product Code: Gray - 65304760 (50lb), 65467550 (25lb)
White - 65304785 (50lb), 65467551 (25lb)
 4. ProSpec Permalastic
Product Code: Gray - 65465001 (50lb)
White - 65465002 (50lb)
 5. ProSpec Permaset 275
Product Code: Gray - 65467505 (50lb)
White - 65467506 (50lb)
 6. ProSpec Permaset 200
Product Code: Gray - 65467505 (50lb)
White - 65467506 (50lb)
 7. ProSpec Medium Bed PermafleX 300
Product Code: Gray – 653000479 (50lb)
White – 65300481 (50lb)
 8. ProSpec Medium Bed Permaset 275
Product Code: Gray – 65462332 (50lb)
White – 65462330 (50lb)

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Various.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Bonsal American, Inc.
8201 Arrowridge Blvd.
Charlotte, NC
28273

Telephone Number: 800-334-0784 Tech Service 8:00 to 5:00 Eastern, Mon.-Fri.

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: CHEMTREC 800-424-9300
INTERNATIONAL + 01-703-527-3887

Date of Preparation: February 1, 2013 **Version #:** 1.1

SAFETY DATA SHEET

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL

Hazard class

Acute toxicity 4 (Oral)
 Skin irritation 2
 Serious eye damage 1
 Skin sensitization 1
 Carcinogenicity 1A
 Specific target organ toxicity - Single exposure 3
 Specific target organ toxicity - Repeated exposure 1

2.2 LABEL ELEMENTS

Hazard Pictogram:



Signal Word:

Danger

Hazard Statement:

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure.

Prevention:

Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust.

Response:

If swallowed: Immediately call a poison center/doctor. Rinse mouth. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Storage:

Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal:

Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified:

Not applicable.

SAFETY DATA SHEET

ProSpec Permafex 300: 33.2 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 ProSpec Permafex 400: 33.6 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 ProSpec Permafex 600: 37.7 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 ProSpec Permalastic: 31.3 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 ProSpec Permaset 275: 31.3 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 ProSpec Permaset 200: 29.8 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 ProSpec Medium Bed Permafex 300: 33.6 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 ProSpec Medium Bed Permaset 275: 31.9 % of the mixture consists of ingredient(s) of unknown acute toxicity.
 This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	UN #	H / F / R / *	CAS No	Wt. %
Silica, crystalline, quartz	Not available.	Not available.	14808-60-7	40 - 70
Portland cement	Not available.	1/0/0	65997-15-1	15 - 40
Calcium carbonate	Not available.	1/0/0	1317-65-3	1 - 5; 5 - 10**
Ferric oxide	UN1376	1/0/0	1309-37-1	3 - 7
Gypsum	UN3077	Not available.	13397-24-5	1 - 5
Magnesium oxide	UN1418	2/0/0	1309-48-4	1 - 5
Calcium oxide	UN1910	3/0/1	1305-78-8	1 - 5

The exact percentage (concentration) of chemicals has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

** ProSpec Permaset 200 contains 1 – 5% Calcium Carbonate. All other products listed in Section 1 contain 5 – 10% Calcium Carbonate.

* Per NOM-018-STPS-2000

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

SAFETY DATA SHEET

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Inhalation: May cause respiratory tract irritation.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Not flammable by WHMIS/OSHA criteria.

5.2 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Treat for surrounding material.

Unsuitable Extinguishing Media: Not available.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

SAFETY DATA SHEET

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

- Methods for Containment:** Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Cleaning-Up:** Vacuum or sweep material and place in a disposal container.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

- Handling:** Avoid contact with skin and eyes. Do not swallow. Good housekeeping is important to prevent accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking. (See section 8)
- General Hygiene Advice:** Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Storage:** Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Ingredient	Occupational Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Silica, crystalline, quartz	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) ((250)/(%SiO ₂ +5) mppcf TWA (resp))	0.025 mg/m ³
Portland cement	15 mg/m ³ (total); 5 mg/m ³ (resp)	1 mg/m ³ (no asbestos and <1% crystalline silica, respirable fraction)
Calcium carbonate	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m ³
Ferric oxide	10 mg/m ³	5 mg/m ³ (iron oxide fume; dust as Fe)
Gypsum	15 mg/m ³ TWA (total dust) 5 mg/m ³ TWA (respirable fraction)	10 mg/m ³
Magnesium oxide	15 mg/m ³	10 mg/m ³
Calcium oxide	5 mg/m ³	2 mg/m ³

8.2 EXPOSURE CONTROLS

- Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Trade Name: ProSpec Permaflex 300 & MB 300
 ProSpec Permaflex 400
 ProSpec Permaflex 600
 ProSpec Permalastic
 ProSpec Permaset 275 & MB 275
 ProSpec Permaset 200

SAFETY DATA SHEET

Eye/Face Protection: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.

Skin Protection:

Hand Protection: Wear suitable waterproof gloves.

Body Protection: Wear suitable waterproof protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Health and Safety Measures: Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder.
Color:	Not available.
Odor:	Not available.
Odor Threshold:	Not available.
Physical State:	Powder.
pH:	12 - 13
Melting Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.
Flammability:	Not Flammable.
Lower Flammability/Explosive Limit:	Not available.
Upper Flammability/Explosive Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density/Specific Gravity:	Not available.
Solubility:	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.

SAFETY DATA SHEET

Percent Volatile, wt. %: Not available.
VOC content, wt. %: 0%, Not applicable; 0 wt, Not applicable.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Incompatible materials. Moisture.

10.5 INCOMPATIBLE MATERIALS

None known.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Skin: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Acute Toxicity:

Ingredient	IDLH	LC50	LD50
Silica, crystalline, quartz	Ca [25 mg/m ³ (cristobalite, tridymite); 50 mg/m ³ (quartz, tripoli)]	Not available.	Oral 500 mg/kg, rat
Portland cement	5000 mg/m ³	Not available.	Not available.
Calcium carbonate	Not available.	Not available.	Not available.
Ferric oxide	2500 mg Fe/m ³	Not available.	Oral >10000 mg/kg, rat
Gypsum	Not available.	Not available.	Not available.

SAFETY DATA SHEET

Magnesium oxide	750 mg/m ³	Not available.	Oral >5000 mg/kg, rat
Calcium oxide	25 mg/m ³	Not available.	Oral 500 mg/kg, rat

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
Not available.	500 – 620 mg/kg, rat	Not available.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Silica, crystalline, quartz	G-A2, I-1, N-1, CP65
Portland cement	G-A4
Calcium carbonate	Not listed.
Ferric oxide	G-A4, I-3
Gypsum	Not listed.
Magnesium oxide	G-A4
Calcium oxide	Not listed.

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

- Skin Corrosion/Irritation:** Causes skin irritation. May cause burns in the presence of moisture.
- Serious Eye Damage/Irritation:** Causes serious eye damage. May cause burns in the presence of moisture.
- Respiratory Sensitization:** Based on available data, the classification criteria are not met.
- Skin Sensitization:** May cause an allergic skin reaction.
- STOT-Single Exposure:** May cause respiratory irritation.
- Chronic Health Effects:** Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
- Carcinogenicity:** May cause cancer.
- Germ Cell Mutagenicity:** This product is not classified as a mutagen.
- Reproductive Toxicity:**
 - Developmental:** Based on available data, the classification criteria are not met.
 - Teratogenicity:** Not hazardous by WHMIS/OSHA criteria.
 - Embryotoxicity:** Not hazardous by WHMIS/OSHA criteria.
 - Fertility:** Based on available data, the classification criteria are not met.
- STOT-Repeated Exposure:** Causes damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

Aspiration Hazard: Based on available data, the classification criteria are not met.

Toxicologically Synergistic Materials: Not available.

Other Information: Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Not available.

Section 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Other disposal recommendations: Not available.

Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER

DOT	TDG	NOM-004-SCT2-1994
Not regulated.	Not regulated.	Not regulated.

14.2 UN PROPER SHIPPING NAME

DOT	TDG	NOM-004-SCT2-1994
Not applicable.	Not applicable.	Not applicable.

14.3 TRANSPORT HAZARD CLASS (ES)

DOT	TDG	NOM-004-SCT2-1994
Not applicable.	Not applicable.	Not applicable.

14.4 PACKING GROUP

DOT	TDG	NOM-004-SCT2-1994
Not applicable.	Not applicable.	Not applicable.

SAFETY DATA SHEET

14.5 ENVIRONMENTAL HAZARDS

Not available.

14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Ferric oxide	Not listed.	Not listed.	Not listed.	Not listed.
Gypsum	Not listed.	Not listed.	Not listed.	Not listed.
Magnesium oxide	Not listed.	Not listed.	Not listed.	Not listed.
Calcium oxide	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Silica, crystalline, quartz	DSL	Yes.
Portland cement	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Ferric oxide	DSL	Yes.
Gypsum	DSL	No.
Magnesium oxide	DSL	Yes.
Calcium oxide	DSL	Yes.

SAFETY DATA SHEET

NFPA - National Fire Protection Association:	
Health:	3
Fire:	1
Reactivity:	0

HMIS - Hazardous Materials Identification System	
Health:	3*
Fire:	1
Reactivity:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme


WHMIS Classification(s):

- Class D2A – Carcinogenicity
- Class D2A - Chronic Toxic Effects
- Class E - Corrosive Material

WHMIS Hazard Symbols:



Mexico Classification:



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

SAFETY DATA SHEET

NTP (N) **National Toxicology Program.**
1 - Known to be carcinogens.
2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation: February 1, 2013

Expiry Date: February 1, 2016

Version: 1.1

Revision Date: February 1, 2013

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com

Prepared for: Bonsal American, Inc.

End of Safety Data Sheet

LABEL ELEMENT REQUIREMENTS

CONFORMING WITH OSHA HAZCOM 2012 STANDARD

Product Identifier

ProSpec Medium Bed Permaflex 300



DANGER

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure.

Do not eat, drink or smoke when using this product. Wash skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. If swallowed: Immediately call a poison center/doctor. Rinse mouth. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents and container in accordance with all local, regional, national and international regulations.

This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

33.6 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Manufacturer/Responsible Party
Bonsal American, Inc.
8201 Arrowridge Blvd.
Charlotte, NC 28273
704-525-1621

Emergency Contact
CHEMTREC 800-424-9300
INTERNATIONAL +01-703-527-3887