

**Safety Data Sheet**

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 09/13/2013

Supersedes: 09/13/2013

Version: 1.0

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product form	: Mixture	
Product name & code	: ProSpec ProColor Plus Grout	Glacier:65462389 - 25lb Honey: 65462390 - 25lb Ice White: 65462391 - 25lb Khaki: 65462392 - 25lb Latte: 65462393 - 25lb Moonlight: 65462394 - 25lb Oyster: 65462395 - 25lb Sahara: 65462396 - 25lb Sand Dollar: 65462397 - 25lb Taupe: 65462398 - 25lb Warm Ivory: 65462399 - 25lb
	Almond: 65462380 - 25lb Beach Sand:65462381 - 25lb Bone: 65462382 - 25lb Buff: 65462383 - 25lb Charcoal: 65462384 - 25lb Dakota Prairie: 65462385 - 25lb Delorean Gray: 65462386 - 25lb Dark Chocolate: 65462387 - 25lb Fawn: 65462388 - 25lb	

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Various.

**1.3. Details of the supplier of the safety data sheet**

Bonsal American, Inc.  
8201 Arrowridge Blvd.  
28273 Charlotte, NC - USA  
T 800-334-0784 Tech Service: Monday - Friday; 8:00am - 5:00pm EST

**1.4. Emergency telephone number**

Emergency number : CHEMTREC (800) 424-9300

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GHS-US classification**

Acute Toxicity 4 (oral)  
Skin Irritation 2  
Serious Eye Damage 1  
Carcinogenicity 1A  
Specific Target Organ Toxicant – Repeated Exposure 1

**2.2. Label elements**

**GHS-US labelling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause cancer. Causes damage to lungs through prolonged or repeated exposure.

Precautionary statements (GHS-US) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. If swallowed: Immediately call a poison center or doctor. Rinse mouth. If exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**2.3. Other hazards**

No additional information available :

**2.4. Unknown acute toxicity (GHS-US)**

ProSpec ProColor Plus Grout (Almond, Beach Sand, Bone, Buff, Charcoa, Dakota Prairie, Dark Chocolate, Delorean Gray, Glacier, Honey, Ice White, Khaki, Latte, Moonlight, Oyster, Sahara, Sand Dollar, and Warm Ivory): 34 % of the mixture consists of ingredient(s) of unknown acute toxicity.

# ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

ProSpec ProColor Plus Grout (Fawn, and Taupe): 33 % of the mixture consists of ingredient(s) of unknown acute toxicity.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Quartz	(CAS No) 14808-60-7	30 - 60	Acute Tox. 4 (Oral), H302 Carc. 1A, H350 STOT RE 1, H372
Cement, alumina, chemicals	(CAS No) 65997-16-2	30 - 60	Skin Irrit. 2, H315 Eye Dam. 1, H318
Titanium dioxide	(CAS No) 13463-67-7	1 - 5*	Acute Tox. 4 (Inhalation), H332 Carc. 2, H351
Vinyl acetate	(CAS No) 108-05-4	1 - 5	Carc. 2, H351

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

\*Ice White

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
- Symptoms/injuries after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : Not available.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

#### 5.3. Advice for firefighters

- Firefighting instructions : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- Protective equipment : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.1.2. For emergency responders

No additional information available

# ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 6.2. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Vacuum or sweep material and place in a disposal container.

### 6.3. Reference to other sections

No information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Do not swallow. Avoid contact with skin and eyes. Avoid generating and breathing dust. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	(30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA, total dust (250)/(%SiO <sub>2</sub> + 5) mppcf TWA, respirable fraction (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA, respirable fraction
Vinyl acetate (108-05-4)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

### 8.2. Exposure controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Hand protection : Wear suitable waterproof gloves.
- Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
- Skin and body protection : Wear suitable waterproof protective clothing.
- Respiratory protection : A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- Other information : Handle according to established industrial hygiene and safety practices. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Powder.
- Colour : Various.
- Odour : Characteristic.
- Odour threshold : No data available.

# ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: No data available.
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

### 9.2. Other information

VOC content : 0%, Not applicable; 0 wt, Not applicable.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Incompatible materials. Moisture.

### 10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

#### Quartz (14808-60-7)

LD50 oral rat	500 mg/kg
---------------	-----------

#### Vinyl acetate (108-05-4)

LD50 oral rat	2920 mg/kg
LD50 dermal rabbit	2320 mg/kg
LC50 inhalation rat	11400 mg/m <sup>3</sup> (4h)

#### Titanium dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

#### ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)

ATE (oral)	>2000 mg/kg
ATE (dermal)	>2000 mg/kg
ATE (inhalation)	> 5 mg/L (4h)

# ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: May cause cancer.

<b>Quartz (14808-60-7)</b>	
IARC group	1
National Toxicity Program (NTP) Status	2

<b>Vinyl acetate (108-05-4)</b>	
IARC group	2B

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B
National Toxicity Program (NTP) Status	1

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Causes damage to lungs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Symptoms/injuries after eye contact	: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.
-------------------	--

### 12.2. Persistence and degradability

<b>ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.
--------------------------------	---

# ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 14: Transport information

In accordance with DOT

#### 14.1. UN number

Not applicable

#### 14.2. UN proper shipping name

Not applicable

#### 14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Cement, alumina, chemicals (65997-16-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### Vinyl acetate (108-05-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 302 Threshold Planning Quantity (TPQ)	1000
--	------

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

##### Titanium dioxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. US State regulations

#### ProSpec ProColor Plus Grout (Almond / Beach Sand / Bone / Buff / Charcoal / Dakota Prairie / Delorean / Gray / Dark / Chocolate / Fawn / Glacier / Honey / Khaki / Latte / Moonlight / Oyster/ Sahara / Sand Dollar / Taupe / Warm Ivory)

State or local regulations	This product contains Crystalline Silica, Quartz and may also contain trace amounts of other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	--


### SECTION 16: Other information

Data sources : SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*